

## Product Data Sheet



Proudly LibraGreen

<b>Product</b>	Acrylic Waterproofing - Fibrous
<b>Product Code</b>	1570
<b>Description</b>	Acrylic Emulsion for use on concrete surfaces, can also be used on suitably prepared metal roofs. Covers hairline cracks on scratch plaster walls
<b>Composition</b>	Styrenated Acrylic, Fibrous Filler, Pigment and Water

### Physical Properties

<b>Colour</b>	Grey
<b>Appearance</b>	glossy
<b>Viscosity</b>	114 KU
<b>Shelf Life</b>	9 months
<b>Storage Conditions</b>	normal
<b>Pack Size</b>	5ℓ, 20ℓ

### Application Properties

<b>Method</b>	brush or roller
<b>Theoretical Coverage (m<sup>2</sup> / ℓ)</b>	2 - 5
<b>Recommended No of Coats</b>	one or two
<b>Drying Time at 25°C</b>	4 hours (touch dry) 6 hours (hard dry)
<b>Overcoating Time at 25°C</b>	overnight
<b>Thinning</b>	Water if necessary
<b>Cleaning Solvent</b>	Water
<b>Recommended System</b>	Use undiluted product, overcoat with Acrylic Roof Paint. Do not apply when rain is imminent

### Precaution

<b>Flashpoint</b>	not applicable
<b>Toxicity</b>	non-toxic

### Note

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.