

## Product Data Sheet



Proudly LibraGreen

<b>Product</b>	Contractors Acrylic
<b>Product Code</b>	188
<b>Description</b>	A good washable Acrylic PVA recommended as a first coat on new ceilings and walls
<b>Composition</b>	Water Based Emulsion
<b><u>Physical Properties</u></b>	
<b>Colour</b>	White
<b>Appearance</b>	matt
<b>Viscosity</b>	heavy bodied
<b>Shelf Life</b>	approximately 12 months
<b>Storage Conditions</b>	normal (protect from frost)
<b>Pack Size</b>	5ℓ, 20ℓ and 200ℓ

### **Application Properties**

<b>Method</b>	roller, brush or airless spray
<b>Theoretical Coverage (m<sup>2</sup> / ℓ)</b>	6 - 8
<b>Recommended No of Coats</b>	one or two depending on surface
<b>Drying Time at 25°C</b>	45 minutes (touch dry) 2 hours (hard dry)
<b>Overcoating Time at 25°C</b>	2 hours
<b>Thinning</b>	ready for use
<b>Cleaning Solvent</b>	water
<b>Recommended System</b>	Apply as a first or a finishing coat on well prepared Interior or External surfaces

### **Precaution**

<b>Flashpoint</b>	Not applicable
<b>Toxicity</b>	non-toxic

### **Note**

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.