

## Product Data Sheet

<b>Product</b>	Floor Coating Enamel
<b>Product Code</b>	605 / 606 / 607 / 608
<b>Description</b>	A high quality floor coating dries to a very hard wearing-stain resistant high gloss finish on concrete floors
<b>Composition</b>	Single Pack Urethane Alkyd

### Physical Properties

<b>Colour</b>	Red, Black, Green and Grey (Standard colours only)
<b>Appearance</b>	high gloss
<b>Viscosity</b>	70 – 72 KU at 25°C
<b>Shelf Life</b>	12 months
<b>Storage Conditions</b>	normal
<b>Pack Size</b>	1ℓ and 5ℓ

### Application Properties

<b>Method</b>	brush or roller
<b>Theoretical Coverage (m<sup>2</sup> / ℓ)</b>	8 - 12
<b>Recommended No of Coats</b>	when surface is porous a 2 <sup>nd</sup> coat is recommended
<b>Drying time at 25°C</b>	2 hour 16 hours (hard dry)
<b>Overcoating time at 25°C</b>	16 hours
<b>Thinning</b>	up to 10% with turpentine
<b>Cleaning solvent</b>	turpentine
<b>Recommended System</b>	Concrete surfaces have to be clean and dry. New concrete surfaces should be 3 months old before painting

### Precaution

<b>Flashpoint</b>	Above 32°
<b>Toxicity</b>	normal in well ventilated areas

### Note

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.