

Product Data Sheet

Product	Sealcote
Product Code	555
Description	This product is a superb glossy, clear dressing that restores the natural depth and colour of brickwork, wood, tiles, steel for interior or exterior surfaces
Composition	Solvent Based Acrylic

Physical Properties

Colour	clear
Appearance	gloss
Viscosity	40 seconds FC4
Shelf Life	approximately 12 months
Storage Conditions	normal
Pack Size	5ℓ

Application Properties

Method	brush
Theoretical Coverage (m² / ℓ)	6 - 8
Recommended No of Coats	one or two depending on porosity of surfaces
Drying time at 25°C	10 – 15 minutes (touch dry) 1 – 2 hours (hard dry)
Overcoating time at 25°C	16 hours
Thinning	ready for use, if necessary thin with Lacquer Thinners
Cleaning solvent	Lacquer Thinners
Recommended System	Apply directly to brickwork, cement work, tiles and steel to bring out the natural colour. Can be used on interior or exterior surfaces

Precaution

Flashpoint	6°C
Toxicity	normal when used in well ventilated areas

Note

THIS PRODUCT IS LEAD FREE

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.