

Product Data Sheet

Product	Super Acrylic PVA
Product Code	120 / 147 / 148 / 1231 / 1232 / 1233 / 1235 / 1237 / 1240 / 1241 / 1242 / 1247 / 1248 / 1249 / 1250 / 1251 / 1252 / 1257 / 1263 / 1265 / 1266 / 1273/ 1275 / 1276 / 1277 / 1278 / 141 / 142 / 143 / 145 / 146 / 147 / 148
Description	A high quality Acrylic PVA for use on Interior or Exterior surfaces where durability is required
Composition	Water Based Emulsion

Physical Properties

Colour	colour card
Appearance	matt
Viscosity	95 – 100 KU
Shelf Life	approximately 12 months
Storage Conditions	normal (protect from frost)
Pack Size	5ℓ, 20ℓ and 200ℓ

Application Properties

Method	brush, roller or airless spray
Theoretical Coverage (m² / ℓ)	6 - 8
Recommended No of Coats	one or two depending on surface
Drying time at 25°C	45 minutes (touch dry) 2 hours (hard dry)
Thinning	not recommended – ready for use
Cleaning solvent	water
Recommended System	Apply as a first or a finishing coat on well prepared and primed surfaces, can be applied as the first coat on interior surfaces

Precaution

Flashpoint	not applicable
Toxicity	non-toxic

Note

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.