

## Product Data Sheet

<b>Product</b>	Sure Seal All Purpose
<b>Product Code</b>	632
<b>Description</b>	Heavy Duty Bitumen based Waterproofing Compound for use with Polycryl on primed or unprimed Concrete surfaces
<b>Composition</b>	Bitumen, Fillers, Organic Solvent

### Physical Properties

<b>Colour</b>	Black
<b>Appearance</b>	glossy
<b>Viscosity</b>	95 KU
<b>Shelf Life</b>	9 months
<b>Storage Conditions</b>	normal
<b>Pack Size</b>	5ℓ, 20ℓ and 200ℓ

### Application Properties

<b>Method</b>	brush or roller
<b>Theoretical Coverage (m<sup>2</sup> / ℓ)</b>	2 - 6
<b>Recommended No of Coats</b>	one or two
<b>Drying Time at 25°C</b>	4 hours (touch dry) 6 hours (hard dry)
<b>Overcoating Time at 25°C</b>	overnight
<b>Thinning</b>	Turpentine if necessary
<b>Cleaning Solvent</b>	Turpentine
<b>Recommended System</b>	Use with Polycryl Membrane to seal cracks on roof or inside farm dams, overcoat with Acrylic Roof if necessary (after 4 weeks from date of last coat of Sureseal)

### Precaution

<b>Flashpoint</b>	38°C
<b>Toxicity</b>	non-toxic when dry

### Note

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.