

Product Data Sheet

Product	Varnish PU Gloss (single pack)
Product Code	550
Description	This product is a one-pack, air drying synthetic varnish which dries to a very tough flexible, high gloss finish on Interior or Exterior Wooden Surfaces
Composition	Urethane Alkyd

Physical Properties

Colour	Clear
Appearance	high-gloss
Viscosity	65 – 70 seconds FC 4
Shelf Life	approximately 12 months
Storage Conditions	normal
Pack Size	1ℓ and 5ℓ

Application Properties

Method	brush
Theoretical Coverage (m² / ℓ)	8 - 10
Recommended No of Coats	one or two
Drying time at 25°C	2 hours (touch dry) 8 hours (surface dry)
Overcoating time at 25°C	16 hours
Thinning	up to 5% with Turpentine if necessary
Cleaning solvent	Turpentine
Recommended System	Wooden surfaces that have been sealed with a sanding sealer can be over coated with this product for better durability. This is a hard wearing product for interior use only

Precaution

Flashpoint	above 32°C
Toxicity	use in well ventilated areas

Note

THIS PRODUCT IS LEAD FREE

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.